



SOUND PANEL SHALLOW MOUNT SPEAKER SYSTEM

RV-FS402

SHALLOW MOUNT 200 WATTS MAX SPEAKER SYSTEM WITH 4" SPEAKERS, TWEETERS AND A PASSIVE RADIATOR



KEY FEATURES

IP65 ENVIRONMENTAL PROTECTION

When mounted correctly, the RV-FS402 speaker is rated IP65 for protection in the harsh RV and Marine environments from the front and rear of the enclosure. Making it perfect for installation on the outside of an RV or vessel.

SHALLOW MOUNT DESIGN

With a mounting depth of only 41mm, the RV-FS402 addresses the age old issue of delivering professional sound quality from a shallow mounting depth that is a requirement in some installations.

QUICK AND SIMPLE INSTALLATION

The RV-FS402 is designed for easy installation, saving time and money. As a stereo pair of speakers, both the left and right speaker wires from the source unit or amplifier only need to be routed to one location for connection, and only a single cut out is required.

PROFESSIONAL SOUND QUALITY

Professional sound quality from FUSION's shallow mount speaker system has been achieved by combining a large surface passive radiator, 2 x 4" speaker drivers and soft dome tweeters all in a perfectly tuned enclosure.

STAINLESS HARDWARE

Stainless steel mounting hardware is included with the RV-FS402. This limits corrosion and tea staining and keeps the RV-FS402 looking great season after season.

TUNED PASSIVE RADIATOR ENCLOSURE

The RV-FS402 utilizes a sealed tuned passive radiator design. This design ensures high quality acoustics in any mounting location.

Where others need enclosures to be constructed, the RV-FS402 is an all inclusive solution. The sealed design protects all drivers and components from being damaged if mounted in cupboards or cavities or outside exposed to the elements.

**FOR MORE INFORMATION VISIT
FUSIONENTERTAINMENT.COM**

DESIGN AND ENGINEERING FEATURES

MULTIPLE MOUNTING SOLUTIONS (OPTIONAL ACCESSORY)

The RV-FS402 speaker has four mounting options available.

FLUSH – With only a 41mm required depth the RV-FS402 will fit flush in most locations.

19MM COMPOSITE WALL DEPTHS – With new technology available in construction the RV-FS402 can be semi mounted into the cavity by using the 22mm spacer.

25MM STANDARD CARAVAN CONSTRUCTION – By using the 16mm spacer the RV-FS402 will semi mount into the normal caravan construction panels.

SURFACE MOUNT – Installs directly onto any flat surface with no cut out required.



PRODUCT INFORMATION

Product Code	Garmin PN	EAN-13 Barcode	Product Code	Garmin PN	EAN-13 Barcode
RV-FS402W	010-01790-00	0753759175078	RV-FS402B	010- 01791-00	0753759175085
RV-FS41SPW	010-12586-00	0753759175108	RV-FS41SPB	010-12587-00	0753759175115
RV-FS22SPW	010-12588-00	0753759175122	RV-FS22SPB	010-12589-00	0753759175139
RV-FS16SPW	010-12590-00	0753759175146	RV-FS16SPB	010-12591-00	0753759175153

SPECIFICATION

Tweeter Type	Soft dome	Impedance	4 Ohms
Max. power (Watts)	100 W (per speaker connection)	Frequency response	70Hz - 20kHz
RMS power (Watts)	25 W (per speaker connection)	Compass-safe distance	TBD
Efficiency (1W/1m)	87dB	Operating temperature	From 0 to 50°C (32 to 122°F)
Min Mounting depth	41 mm (1.65 in.)	Storage temperature	From -20 to 70°C (-4 to 158°F)

SPEAKER DIMENSIONS

